

L Number	Hits	Search Text	DB	Time stamp
1	0	"base transceiver station" and "graded packet" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:07
2	21	"base transceiver station" and "packet" and "metric" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:08
3	0	"base transceiver station" and "graded packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:08
4	0	"base transceiver station" and "mixed packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:09
5	0	"base transceiver station" and "redundant packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:09
6	0	"base transceiver station" and "redundant packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:10
7	173	"base transceiver station" and "packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:10
8	0	"base transceiver station" and "redundant packet selection" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:11
9	0	"redundant packet selection" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:11

10	17167	((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:07
11	0	((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "graded packet" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:08
12	12	((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "packet" and "metric" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:08
13	0	((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "graded packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:08

14	0	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "mixed packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:09
15	0	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "redundant packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:09
16	0	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "redundant packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:10
17	72	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "packet" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:10

18	0	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "base transceiver station" and "redundant packet selection" and (metric or "bit error rate" or "carrier to noise ratio" or "signal to noise ratio" or "signal strength") and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:11
19	0	(((370/216) or (370/229) or (370/241) or (370/252) or (370/335) or (370/336) or (370/429) or (370/329) or (370/342) or (370/332) or (370/320) or (370/441) or (370/60) or (370/94.1) or (455/452.2) or (455/525) or (455/524) or (455/436-439) or (455/517) or (455/456.5) or (455/456.6) or (455/115.3) or (455/132-138) or (455/226.2) or (455/226.3)).CCLS.) and "redundant packet selection" and @ad<20010321	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/27 16:11